

NAME

CPANPLUS::Internals::Utils

SYNOPSIS

```
my $bool = $cb->_mkdir( dir => 'blah' );
my $bool = $cb->_chdir( dir => 'blah' );
my $bool = $cb->_rmdir( dir => 'blah' );

my $bool = $cb->_move( from => '/some/file', to => '/other/file' );
my $bool = $cb->_move( from => '/some/dir', to => '/other/dir' );

my $cont = $cb->_get_file_contents( file => '/path/to/file' );

my $version = $cb->_perl_version( perl => $^X );
```

DESCRIPTION

CPANPLUS::Internals::Utils holds a few convenience functions for CPANPLUS libraries.

METHODS

`$cb->_mkdir( dir => '/some/dir' )`

`_mkdir` creates a full path to a directory.

Returns true on success, false on failure.

`$cb->_chdir( dir => '/some/dir' )`

`_chdir` changes directory to a dir.

Returns true on success, false on failure.

`$cb->_rmdir( dir => '/some/dir' );`

Removes a directory completely, even if it is non-empty.

Returns true on success, false on failure.

`$cb->_perl_version ( perl => 'some/perl/binary' );`

`_perl_version` returns the version of a certain perl binary. It does this by actually running a command.

Returns the perl version on success and false on failure.

`$cb->_version_to_number( version => $version );`

Returns a proper module version, or '0.0' if none was available.

`$cb->_whoami`

Returns the name of the subroutine you're currently in.

`_get_file_contents( file => $file );`

Returns the contents of a file

Moves a file or directory to the target.

Returns true on success, false on failure.

Moves a file or directory to the target.

Returns true on success, false on failure.

`$cb->_mode_plus_w( file => '/path/to/file' );`

Sets the +w bit for the file.

Returns true on success, false on failure.

`$uri = $cb->_host_to_uri( scheme => SCHEME, host => HOST, path => PATH );`

Turns a CPANPLUS::Config style host entry into an URI string.

Returns the uri on success, and false on failure

`$cb->_vcmp( VERSION, VERSION );`

Normalizes the versions passed and does a '<=>' on them, returning the result.

`$cb->_home_dir`

Returns the user's homedir, or cwd if it could not be found

`$path = $cb->_safe_path( path => $path );`

Returns a path that's safe to us on Win32 and VMS.

Only cleans up the path on Win32 if the path exists.

On VMS, it encodes dots to _ using VMS::Filespec::vmsify

`($pkg, $version, $ext) = $cb->_split_package_string( package => PACKAGE_STRING );`

Splits the name of a CPAN package string up in it's package, version and extension parts.

For example, Foo-Bar-1.2.tar.gz would return the following parts:

Package:	Foo-Bar
Version:	1.2
Extension:	tar.gz