

NAME

Filter::Util::Call - Perl Source Filter Utility Module

SYNOPSIS

```
use Filter::Util::Call ;
```

DESCRIPTION

This module provides you with the framework to write *Source Filters* in Perl.

An alternate interface to Filter::Util::Call is now available. See *Filter::Simple* for more details.

A *Perl Source Filter* is implemented as a Perl module. The structure of the module can take one of two broadly similar formats. To distinguish between them, the first will be referred to as *method filter* and the second as *closure filter*.

Here is a skeleton for the *method filter*:

```
package MyFilter ;

use Filter::Util::Call ;

sub import
{
    my($type, @arguments) = @_ ;
    filter_add([]) ;
}

sub filter
{
    my($self) = @_ ;
    my($status) ;

    $status = filter_read() ;
    $status ;
}

1 ;
```

and this is the equivalent skeleton for the *closure filter*:

```
package MyFilter ;

use Filter::Util::Call ;

sub import
{
    my($type, @arguments) = @_ ;

    filter_add(
        sub
        {
            my($status) ;
            $status = filter_read() ;
            $status ;
        }
    ) ;
}
```

```
        } )  
    }  
  
    1 ;
```

To make use of either of the two filter modules above, place the line below in a Perl source file.

```
use MyFilter;
```

In fact, the skeleton modules shown above are fully functional *Source Filters*, albeit fairly useless ones. All they does is filter the source stream without modifying it at all.

As you can see both modules have a broadly similar structure. They both make use of the `Filter::Util::Call` module and both have an `import` method. The difference between them is that the *method filter* requires a *filter* method, whereas the *closure filter* gets the equivalent of a *filter* method with the anonymous sub passed to *filter_add*.

To make proper use of the *closure filter* shown above you need to have a good understanding of the concept of a *closure*. See *perlref* for more details on the mechanics of *closures*.

use Filter::Util::Call

The following functions are exported by `Filter::Util::Call`:

```
filter_add()  
filter_read()  
filter_read_exact()  
filter_del()
```

import()

The `import` method is used to create an instance of the filter. It is called indirectly by Perl when it encounters the `use MyFilter` line in a source file (See "*import*" in *perlfunc* for more details on `import`).

It will always have at least one parameter automatically passed by Perl - this corresponds to the name of the package. In the example above it will be "MyFilter".

Apart from the first parameter, `import` can accept an optional list of parameters. These can be used to pass parameters to the filter. For example:

```
use MyFilter qw(a b c) ;
```

will result in the `@_` array having the following values:

```
@_ [0] => "MyFilter"  
@_ [1] => "a"  
@_ [2] => "b"  
@_ [3] => "c"
```

Before terminating, the `import` function must explicitly install the filter by calling `filter_add`.

filter_add()

The function, `filter_add`, actually installs the filter. It takes one parameter which should be a reference. The kind of reference used will dictate which of the two filter types will be used.

If a CODE reference is used then a *closure filter* will be assumed.

If a CODE reference is not used, a *method filter* will be assumed. In a *method filter*, the reference can

be used to store context information. The reference will be *blessed* into the package by `filter_add`.

See the filters at the end of this documents for examples of using context information using both *method filters* and *closure filters*.

filter() and anonymous sub

Both the `filter` method used with a *method filter* and the anonymous sub used with a *closure filter* is where the main processing for the filter is done.

The big difference between the two types of filter is that the *method filter* uses the object passed to the method to store any context data, whereas the *closure filter* uses the lexical variables that are maintained by the closure.

Note that the single parameter passed to the *method filter*, `$self`, is the same reference that was passed to `filter_add` blessed into the filter's package. See the example filters later on for details of using `$self`.

Here is a list of the common features of the anonymous sub and the `filter()` method.

`$_`

Although `$_` doesn't actually appear explicitly in the sample filters above, it is implicitly used in a number of places.

Firstly, when either `filter` or the anonymous sub are called, a local copy of `$_` will automatically be created. It will always contain the empty string at this point.

Next, both `filter_read` and `filter_read_exact` will append any source data that is read to the end of `$_`.

Finally, when `filter` or the anonymous sub are finished processing, they are expected to return the filtered source using `$_`.

This implicit use of `$_` greatly simplifies the filter.

`$status`

The status value that is returned by the user's `filter` method or anonymous sub and the `filter_read` and `read_exact` functions take the same set of values, namely:

```
< 0  Error
= 0  EOF
> 0  OK
```

`filter_read` and `filter_read_exact`

These functions are used by the filter to obtain either a line or block from the next filter in the chain or the actual source file if there aren't any other filters.

The function `filter_read` takes two forms:

```
$status = filter_read() ;
$status = filter_read($size) ;
```

The first form is used to request a *line*, the second requests a *block*.

In line mode, `filter_read` will append the next source line to the end of the `$_` scalar.

In block mode, `filter_read` will append a block of data which is `<= $size` to the end of the `$_` scalar. It is important to emphasise the that `filter_read` will not necessarily read a block which is *precisely* `$size` bytes.

If you need to be able to read a block which has an exact size, you can use the function `filter_read_exact`. It works identically to `filter_read` in block mode, except it will try to read a block which is exactly `$size` bytes in length. The only circumstances when it will not return a block which is `$size` bytes long is on EOF or error.

It is very important to check the value of `$status` after every call to `filter_read` or `filter_read_exact`.

filter_del

The function, `filter_del`, is used to disable the current filter. It does not affect the running of the filter. All it does is tell Perl not to call filter any more.

See *Example 4: Using filter_del* for details.

EXAMPLES

Here are a few examples which illustrate the key concepts - as such most of them are of little practical use.

The examples sub-directory has copies of all these filters implemented both as *method filters* and as *closure filters*.

Example 1: A simple filter.

Below is a *method filter* which is hard-wired to replace all occurrences of the string "Joe" to "Jim". Not particularly Useful, but it is the first example and I wanted to keep it simple.

```
package Joe2Jim ;

use Filter::Util::Call ;

sub import
{
    my($type) = @_ ;

    filter_add(bless []) ;
}

sub filter
{
    my($self) = @_ ;
    my($status) ;

    s/Joe/Jim/g
    if ($status = filter_read()) > 0 ;
    $status ;
}

1 ;
```

Here is an example of using the filter:

```
use Joe2Jim ;
print "Where is Joe?\n" ;
```

And this is what the script above will print:

```
Where is Jim?
```

Example 2: Using the context

The previous example was not particularly useful. To make it more general purpose we will make use of the context data and allow any arbitrary *from* and *to* strings to be used. This time we will use a

closure filter. To reflect its enhanced role, the filter is called Subst.

```
package Subst ;

use Filter::Util::Call ;
use Carp ;

sub import
{
    croak("usage: use Subst qw(from to)")
        unless @_ == 3 ;
    my ($self, $from, $to) = @_ ;
    filter_add(
        sub
        {
            my ($status) ;
            s/$from/$to/
                if ($status = filter_read()) > 0 ;
            $status ;
        })
    ;
    1 ;
}
```

and is used like this:

```
use Subst qw(Joe Jim) ;
print "Where is Joe?\n" ;
```

Example 3: Using the context within the filter

Here is a filter which a variation of the Joe2Jim filter. As well as substituting all occurrences of "Joe" to "Jim" it keeps a count of the number of substitutions made in the context object.

Once EOF is detected (\$status is zero) the filter will insert an extra line into the source stream. When this extra line is executed it will print a count of the number of substitutions actually made. Note that \$status is set to 1 in this case.

```
package Count ;

use Filter::Util::Call ;

sub filter
{
    my ($self) = @_ ;
    my ($status) ;

    if (($status = filter_read()) > 0 ) {
        s/Joe/Jim/g ;
        ++ $$self ;
    }
    elsif ($$self >= 0) { # EOF
        $_ = "print q[Made ${$self} substitutions\n]" ;
        $status = 1 ;
        $$self = -1 ;
    }
}
```

```
        $status ;
    }

    sub import
    {
        my ($self) = @_ ;
        my ($count) = 0 ;
        filter_add(\ $count) ;
    }

    1 ;
```

Here is a script which uses it:

```
use Count ;
print "Hello Joe\n" ;
print "Where is Joe\n" ;
```

Outputs:

```
Hello Jim
Where is Jim
Made 2 substitutions
```

Example 4: Using filter_del

Another variation on a theme. This time we will modify the Subst filter to allow a starting and stopping pattern to be specified as well as the *from* and *to* patterns. If you know the *vi* editor, it is the equivalent of this command:

```
:/start/,/stop/s/from/to/
```

When used as a filter we want to invoke it like this:

```
use NewSubst qw(start stop from to) ;
```

Here is the module.

```
package NewSubst ;

use Filter::Util::Call ;
use Carp ;

sub import
{
    my ($self, $start, $stop, $from, $to) = @_ ;
    my ($found) = 0 ;
    croak("usage: use Subst qw(start stop from to)")
        unless @_ == 5 ;

    filter_add(
        sub
        {
            my ($status) ;
```

```
    if (($status = filter_read()) > 0) {  
  
        $found = 1  
        if $found == 0 and /$start/ ;  
  
        if ($found) {  
            s/$from/$to/ ;  
            filter_del() if /$stop/ ;  
        }  
  
    }  
    $status ;  
} )  
  
}  
  
1 ;
```

Filter::Simple

If you intend using the Filter::Call functionality, I would strongly recommend that you check out Damian Conway's excellent Filter::Simple module. Damian's module provides a much cleaner interface than Filter::Util::Call. Although it doesn't allow the fine control that Filter::Util::Call does, it should be adequate for the majority of applications. It's available at

http://www.cpan.org/modules/by-author/Damian_Conway/Filter-Simple.tar.gz
<http://www.csse.monash.edu.au/~damian/CPAN/Filter-Simple.tar.gz>

AUTHOR

Paul Marquess

DATE

26th January 1996