

NAME

perlfaq9 - Networking (\$Revision: 1.28 \$, \$Date: 2005/12/31 00:54:37 \$)

DESCRIPTION

This section deals with questions related to networking, the internet, and a few on the web.

What is the correct form of response from a CGI script?

(Alan Flavell <flavell+www@a5.ph.gla.ac.uk> answers...)

The Common Gateway Interface (CGI) specifies a software interface between a program ("CGI script") and a web server (HTTPD). It is not specific to Perl, and has its own FAQs and tutorials, and usenet group, comp.infosystems.www.authoring.cgi

The CGI specification is outlined in an informational RFC: <http://www.ietf.org/rfc/rfc3875>

Other relevant documentation listed in: http://www.perl.org/CGI_MetaFAQ.html

These Perl FAQs very selectively cover some CGI issues. However, Perl programmers are strongly advised to use the CGI.pm module, to take care of the details for them.

The similarity between CGI response headers (defined in the CGI specification) and HTTP response headers (defined in the HTTP specification, RFC2616) is intentional, but can sometimes be confusing.

The CGI specification defines two kinds of script: the "Parsed Header" script, and the "Non Parsed Header" (NPH) script. Check your server documentation to see what it supports. "Parsed Header" scripts are simpler in various respects. The CGI specification allows any of the usual newline representations in the CGI response (it's the server's job to create an accurate HTTP response based on it). So "\n" written in text mode is technically correct, and recommended. NPH scripts are more tricky: they must put out a complete and accurate set of HTTP transaction response headers; the HTTP specification calls for records to be terminated with carriage-return and line-feed, i.e ASCII \015\012 written in binary mode.

Using CGI.pm gives excellent platform independence, including EBCDIC systems. CGI.pm selects an appropriate newline representation (\$CGI::CRLF) and sets binmode as appropriate.

My CGI script runs from the command line but not the browser. (500 Server Error)

Several things could be wrong. You can go through the "Troubleshooting Perl CGI scripts" guide at

http://www.perl.org/troubleshooting_CGI.html

If, after that, you can demonstrate that you've read the FAQs and that your problem isn't something simple that can be easily answered, you'll probably receive a courteous and useful reply to your question if you post it on comp.infosystems.www.authoring.cgi (if it's something to do with HTTP or the CGI protocols). Questions that appear to be Perl questions but are really CGI ones that are posted to comp.lang.perl.misc are not so well received.

The useful FAQs, related documents, and troubleshooting guides are listed in the CGI Meta FAQ:

http://www.perl.org/CGI_MetaFAQ.html

How can I get better error messages from a CGI program?

Use the CGI::Carp module. It replaces `warn` and `die`, plus the normal Carp modules `carp`, `croak`, and `confess` functions with more verbose and safer versions. It still sends them to the normal server error log.

```
use CGI::Carp;
warn "This is a complaint";
die "But this one is serious";
```



```
<B>You can't see me!</B>
-->
```

How do I extract URLs?

You can easily extract all sorts of URLs from HTML with `HTML::SimpleLinkExtor` which handles anchors, images, objects, frames, and many other tags that can contain a URL. If you need anything more complex, you can create your own subclass of `HTML::LinkExtor` or `HTML::Parser`. You might even use `HTML::SimpleLinkExtor` as an example for something specifically suited to your needs.

You can use `URI::Find` to extract URLs from an arbitrary text document.

Less complete solutions involving regular expressions can save you a lot of processing time if you know that the input is simple. One solution from Tom Christiansen runs 100 times faster than most module based approaches but only extracts URLs from anchors where the first attribute is HREF and there are no other attributes.

```
#!/usr/bin/perl -n00
# qxurl - tchrist@perl.com
print "$2\n" while m{
    < \s*
      A \s+ HREF \s* = \s* (["']) (.*?) \1
    \s* >
}gsix;
```

How do I download a file from the user's machine? How do I open a file on another machine?

In this case, download means to use the file upload feature of HTML forms. You allow the web surfer to specify a file to send to your web server. To you it looks like a download, and to the user it looks like an upload. No matter what you call it, you do it with what's known as **multipart/form-data** encoding. The `CGI.pm` module (which comes with Perl as part of the Standard Library) supports this in the `start_multipart_form()` method, which isn't the same as the `startform()` method.

See the section in the `CGI.pm` documentation on file uploads for code examples and details.

How do I make a pop-up menu in HTML?

Use the `<SELECT>` and `<OPTION>` tags. The `CGI.pm` module (available from CPAN) supports this widget, as well as many others, including some that it cleverly synthesizes on its own.

How do I fetch an HTML file?

One approach, if you have the lynx text-based HTML browser installed on your system, is this:

```
$html_code = `lynx -source $url`;
$text_data = `lynx -dump $url`;
```

The `libwww-perl` (LWP) modules from CPAN provide a more powerful way to do this. They don't require lynx, but like lynx, can still work through proxies:

```
# simplest version
use LWP::Simple;
$content = get($URL);

# or print HTML from a URL
use LWP::Simple;
getprint "http://www.linpro.no/lwp/";

# or print ASCII from HTML from a URL
```

```
# also need HTML-Tree package from CPAN
use LWP::Simple;
use HTML::Parser;
use HTML::FormatText;
my ($html, $ascii);
$html = get("http://www.perl.com/");
defined $html
    or die "Can't fetch HTML from http://www.perl.com/";
$ascii = HTML::FormatText->new->format(parse_html($html));
print $ascii;
```

How do I automate an HTML form submission?

If you are doing something complex, such as moving through many pages and forms or a web site, you can use `WWW::Mechanize`. See its documentation for all the details.

If you're submitting values using the GET method, create a URL and encode the form using the `query_form` method:

```
use LWP::Simple;
use URI::URL;

my $url = url('http://www.perl.com/cgi-bin/cpan_mod');
$url->query_form(module => 'DB_File', readme => 1);
$content = get($url);
```

If you're using the POST method, create your own user agent and encode the content appropriately.

```
use HTTP::Request::Common qw(POST);
use LWP::UserAgent;

my $ua = LWP::UserAgent->new();
my $req = POST 'http://www.perl.com/cgi-bin/cpan_mod',
    [ module => 'DB_File', readme => 1 ];
$content = $ua->request($req)->as_string;
```

How do I decode or create those %-encodings on the web?

If you are writing a CGI script, you should be using the `CGI.pm` module that comes with perl, or some other equivalent module. The `CGI` module automatically decodes queries for you, and provides an `escape()` function to handle encoding.

The best source of detailed information on URI encoding is RFC 2396. Basically, the following substitutions do it:

```
s/([^\w()*~!.-])/sprintf '%02x', ord $1/eg;    # encode

s/%([A-Za-f\d]{2})/chr hex $1/eg;            # decode
s/%([:xdigit:]{2})/chr hex $1/eg;           # same thing
```

However, you should only apply them to individual URI components, not the entire URI, otherwise you'll lose information and generally mess things up. If that didn't explain it, don't worry. Just go read section 2 of the RFC, it's probably the best explanation there is.

RFC 2396 also contains a lot of other useful information, including a regexp for breaking any arbitrary URI into components (Appendix B).

How do I redirect to another page?

Specify the complete URL of the destination (even if it is on the same server). This is one of the two different kinds of CGI "Location:" responses which are defined in the CGI specification for a Parsed Headers script. The other kind (an absolute URLpath) is resolved internally to the server without any HTTP redirection. The CGI specifications do not allow relative URLs in either case.

Use of CGI.pm is strongly recommended. This example shows redirection with a complete URL. This redirection is handled by the web browser.

```
use CGI qw/:standard/;

my $url = 'http://www.cpan.org/';
print redirect($url);
```

This example shows a redirection with an absolute URLpath. This redirection is handled by the local web server.

```
my $url = '/CPAN/index.html';
print redirect($url);
```

But if coded directly, it could be as follows (the final "\n" is shown separately, for clarity), using either a complete URL or an absolute URLpath.

```
print "Location: $url\n";    # CGI response header
print "\n";                  # end of headers
```

How do I put a password on my web pages?

To enable authentication for your web server, you need to configure your web server. The configuration is different for different sorts of web servers---apache does it differently from iPlanet which does it differently from IIS. Check your web server documentation for the details for your particular server.

How do I edit my .htpasswd and .htgroup files with Perl?

The HTTPD::UserAdmin and HTTPD::GroupAdmin modules provide a consistent OO interface to these files, regardless of how they're stored. Databases may be text, dbm, Berkeley DB or any database with a DBI compatible driver. HTTPD::UserAdmin supports files used by the "Basic" and "Digest" authentication schemes. Here's an example:

```
use HTTPD::UserAdmin ();
HTTPD::UserAdmin
->new(DB => "/foo/.htpasswd")
->add($username => $password);
```

How do I make sure users can't enter values into a form that cause my CGI script to do bad things?

See the security references listed in the CGI Meta FAQ

http://www.perl.org/CGI_MetaFAQ.html

How do I parse a mail header?

For a quick-and-dirty solution, try this solution derived from "split" in perlfunc:

```
$/ = '';
$header = <MSG>;
$header =~ s/\n\s+/ /g; # merge continuation lines
```

```
%head = ( UNIX_FROM_LINE, split /^( [-\w]+ ): \s* /m, $header );
```

That solution doesn't do well if, for example, you're trying to maintain all the Received lines. A more complete approach is to use the Mail::Header module from CPAN (part of the MailTools package).

How do I decode a CGI form?

(contributed by brian d foy)

Use the CGI.pm module that comes with Perl. It's quick, it's easy, and it actually does quite a bit of work to ensure things happen correctly. It handles GET, POST, and HEAD requests, multipart forms, multivalued fields, query string and message body combinations, and many other things you probably don't want to think about.

It doesn't get much easier: the CGI module automatically parses the input and makes each value available through the `param()` function.

```
use CGI qw(:standard);

my $total = param( 'price' ) + param( 'shipping' );

my @items = param( 'item' ); # multiple values, same field name
```

If you want an object-oriented approach, CGI.pm can do that too.

```
use CGI;

my $cgi = CGI->new();

my $total = $cgi->param( 'price' ) + $cgi->param( 'shipping' );

my @items = $cgi->param( 'item' );
```

You might also try CGI::Minimal which is a lightweight version of the same thing. Other CGI::* modules on CPAN might work better for you, too.

Many people try to write their own decoder (or copy one from another program) and then run into one of the many "gotchas" of the task. It's much easier and less hassle to use CGI.pm.

How do I check a valid mail address?

You can't, at least, not in real time. Bummer, eh?

Without sending mail to the address and seeing whether there's a human on the other end to answer you, you cannot determine whether a mail address is valid. Even if you apply the mail header standard, you can have problems, because there are deliverable addresses that aren't RFC-822 (the mail header standard) compliant, and addresses that aren't deliverable which are compliant.

You can use the Email::Valid or RFC::RFC822::Address which check the format of the address, although they cannot actually tell you if it is a deliverable address (i.e. that mail to the address will not bounce). Modules like Mail::CheckUser and Mail::EXPN try to interact with the domain name system or particular mail servers to learn even more, but their methods do not work everywhere---especially for security conscious administrators.

Many are tempted to try to eliminate many frequently-invalid mail addresses with a simple regex, such as `/^[\w.-]+ \@ (? : [\w-]+ \.)+ \w+ $ /`. It's a very bad idea. However, this also throws out many valid ones, and says nothing about potential deliverability, so it is not suggested. Instead, see http://www.cpan.org/authors/Tom_Christiansen/scripts/ckaddr.gz, which actually checks against the

full RFC spec (except for nested comments), looks for addresses you may not wish to accept mail to (say, Bill Clinton or your postmaster), and then makes sure that the hostname given can be looked up in the DNS MX records. It's not fast, but it works for what it tries to do.

Our best advice for verifying a person's mail address is to have them enter their address twice, just as you normally do to change a password. This usually weeds out typos. If both versions match, send mail to that address with a personal message that looks somewhat like:

```
Dear someuser@host.com,
```

```
Please confirm the mail address you gave us Wed May 6 09:38:41
MDT 1998 by replying to this message. Include the string
"Rumpelstiltskin" in that reply, but spelled in reverse; that is,
start with "Nik...". Once this is done, your confirmed address will
be entered into our records.
```

If you get the message back and they've followed your directions, you can be reasonably assured that it's real.

A related strategy that's less open to forgery is to give them a PIN (personal ID number). Record the address and PIN (best that it be a random one) for later processing. In the mail you send, ask them to include the PIN in their reply. But if it bounces, or the message is included via a "vacation" script, it'll be there anyway. So it's best to ask them to mail back a slight alteration of the PIN, such as with the characters reversed, one added or subtracted to each digit, etc.

How do I decode a MIME/BASE64 string?

The MIME-Base64 package (available from CPAN) handles this as well as the MIME/QP encoding. Decoding BASE64 becomes as simple as:

```
use MIME::Base64;
$decoded = decode_base64($encoded);
```

The MIME-Tools package (available from CPAN) supports extraction with decoding of BASE64 encoded attachments and content directly from email messages.

If the string to decode is short (less than 84 bytes long) a more direct approach is to use the `unpack()` function's "u" format after minor transliterations:

```
tr#A-Za-z0-9+/#cd;          # remove non-base64 chars
tr#A-Za-z0-9+/#_#;         # convert to uuencoded format
$len = pack("c", 32 + 0.75*length); # compute length byte
print unpack("u", $len . $_); # uudecode and print
```

How do I return the user's mail address?

On systems that support `getpwuid`, the `$<` variable, and the `Sys::Hostname` module (which is part of the standard perl distribution), you can probably try using something like this:

```
use Sys::Hostname;
$address = sprintf('%s@%s', scalar getpwuid($<), hostname);
```

Company policies on mail address can mean that this generates addresses that the company's mail system will not accept, so you should ask for users' mail addresses when this matters. Furthermore, not all systems on which Perl runs are so forthcoming with this information as is Unix.

The `Mail::Util` module from CPAN (part of the MailTools package) provides a `mailaddress()` function that tries to guess the mail address of the user. It makes a more intelligent guess than the code above, using information given when the module was installed, but it could still be incorrect. Again,

the best way is often just to ask the user.

How do I send mail?

Use the `sendmail` program directly:

```
open(SENDMAIL, "|/usr/lib/sendmail -oi -t -odq")
    or die "Can't fork for sendmail: $!\n";
print SENDMAIL <<"EOF";
From: User Originating Mail <me\@host>
To: Final Destination <you\@otherhost>
Subject: A relevant subject line

Body of the message goes here after the blank line
in as many lines as you like.
EOF
close(SENDMAIL)    or warn "sendmail didn't close nicely";
```

The `-oi` option prevents `sendmail` from interpreting a line consisting of a single dot as "end of message". The `-t` option says to use the headers to decide who to send the message to, and `-odq` says to put the message into the queue. This last option means your message won't be immediately delivered, so leave it out if you want immediate delivery.

Alternate, less convenient approaches include calling `mail` (sometimes called `mailx`) directly or simply opening up port 25 have having an intimate conversation between just you and the remote SMTP daemon, probably `sendmail`.

Or you might be able use the CPAN module `Mail::Mailer`:

```
use Mail::Mailer;

$mailer = Mail::Mailer->new();
$mailer->open({ From    => $from_address,
               To      => $to_address,
               Subject => $subject,
               })
    or die "Can't open: $!\n";
print $mailer $body;
$mailer->close();
```

The `Mail::Internet` module uses `Net::SMTP` which is less Unix-centric than `Mail::Mailer`, but less reliable. Avoid raw SMTP commands. There are many reasons to use a mail transport agent like `sendmail`. These include queuing, MX records, and security.

How do I use MIME to make an attachment to a mail message?

This answer is extracted directly from the `MIME::Lite` documentation. Create a multipart message (i.e., one with attachments).

```
use MIME::Lite;

### Create a new multipart message:
$msg = MIME::Lite->new(
    From    => 'me@myhost.com',
    To      => 'you@yourhost.com',
    Cc      => 'some@other.com, some@more.com',
    Subject => 'A message with 2 parts...',
    Type    => 'multipart/mixed'
```



```

    );

    ### Add parts (each "attach" has same arguments as "new"):
    $msg->attach(Type    =>'TEXT',
                Data    =>"Here's the GIF file you wanted"
                );
    $msg->attach(Type    =>'image/gif',
                Path    =>'aaa000123.gif',
                Filename =>'logo.gif'
                );

    $text = $msg->as_string;

```

MIME::Lite also includes a method for sending these things.

```
$msg->send;
```

This defaults to using *sendmail* but can be customized to use SMTP via *Net::SMTP*.

How do I read mail?

While you could use the Mail::Folder module from CPAN (part of the MailFolder package) or the Mail::Internet module from CPAN (part of the MailTools package), often a module is overkill. Here's a mail sorter.

```

#!/usr/bin/perl

my(@msgs, @sub);
my $msgno = -1;
$/ = '';                                # paragraph reads
while (<>) {
    if (/^From /m) {
        /^Subject:\s*(?:Re:\s*)*(.*)/mi;
        $sub[++$msgno] = lc($1) || '';
    }
    $msgs[$msgno] .= $_;
}
for my $i (sort { $sub[$a] cmp $sub[$b] || $a <=> $b } (0 .. $#msgs)) {
    print $msgs[$i];
}

```

Or more succinctly,

```

#!/usr/bin/perl -n00
# bysub2 - awkish sort-by-subject
BEGIN { $msgno = -1 }
$sub[++$msgno] = (/^Subject:\s*(?:Re:\s*)*(.*)/mi)[0] if /^From/m;
$msg[$msgno] .= $_;
END { print @msg[ sort { $sub[$a] cmp $sub[$b] || $a <=> $b } (0 ..
$msg) ] }

```

How do I find out my hostname, domainname, or IP address?

(contributed by brian d foy)

The Net::Domain module, which is part of the standard distribution starting in perl5.7.3, can get you the fully qualified domain name (FQDN), the host name, or the domain name.

```
use Net::Domain qw(hostname hostfqdn hostdomain);

my $host = hostfqdn();
```

The `Sys::Hostname` module, included in the standard distribution since perl5.6, can also get the hostname.

```
use Sys::Hostname;

$host = hostname();
```

To get the IP address, you can use the `gethostbyname` built-in function to turn the name into a number. To turn that number into the dotted octet form (a.b.c.d) that most people expect, use the `inet_ntoa` function from the `<Socket>` module, which also comes with perl.

```
use Socket;

my $address = inet_ntoa(
    scalar gethostbyname( $host || 'localhost' )
);
```

How do I fetch a news article or the active newsgroups?

Use the `Net::NNTP` or `News::NNTPClient` modules, both available from CPAN. This can make tasks like fetching the newsgroup list as simple as

```
perl -MNews::NNTPClient
    -e 'print News::NNTPClient->new->list("newsgroups")'
```

How do I fetch/put an FTP file?

`LWP::Simple` (available from CPAN) can fetch but not put. `Net::FTP` (also available from CPAN) is more complex but can put as well as fetch.

How can I do RPC in Perl?

(Contributed by brian d foy)

Use one of the RPC modules you can find on CPAN (<http://search.cpan.org/search?query=RPC&mode=all>).

AUTHOR AND COPYRIGHT

Copyright (c) 1997-2006 Tom Christiansen, Nathan Torkington, and other authors as noted. All rights reserved.

This documentation is free; you can redistribute it and/or modify it under the same terms as Perl itself.

Irrespective of its distribution, all code examples in this file are hereby placed into the public domain. You are permitted and encouraged to use this code in your own programs for fun or for profit as you see fit. A simple comment in the code giving credit would be courteous but is not required.